



Product Service

# CERTIFICATE

No. Z2 022757 1162 Rev. 01

**Holder of Certificate:** **HAGS Aneby AB**

Grännavägen 7  
578 23 Aneby  
SWEDEN

**Certification Mark:**



**Product:** **Playground equipment  
NRG + Slackline components**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 713319017-03

**Valid until:** 2028-03-07

**Date,** 2024-03-04

( Tobias Hofmann )

# CERTIFICATE

No. Z2 022757 1162 Rev. 01

**Model(s):** Amazon Basin, Angel Cascade, Atlas, Bermuda Triangle, Cape Horn, Cheddar Gorge, Double Klondike, Everglades, Funnel-web, Gaping Ghyll, Giants Causeway, Grand Canon, Hogs Back, Jacobs Ladder, Jungle Rope, Kakum Canopy Walk, Klondike, ULURU , Magellan Straits, Niagara Falls, Offas Dyke, Okavango Swamp, Pillars of Hercules, Ross Ice Shelf, Sierra Diablo, Single Rope, Slackline 2m jungle rope, Slackline 2 m rope, Slackline 3 m rope, Slackline 4 m rope, Slackline platform, Tierra Del Fuego, Triangle Net, Twisted Ladder, Kebnekaise , Galdhøpiggen, Yukon Log Roll, Durdle Door, Malham Cove

**Parameters:** Climbing and balancing climbing trail equipment.  
Can provided as standard and bespoke combinations.

Materials:  
Steel tubes 88.9 mm or 127 mm diameter, with powder coated finished. Ropes and nets are made from diameter 16 mm, 18 mm or 24 mm nylon covered with steel core.  
Sliding tube from Stainless Steel. Panels from HDPE.  
Step posts from recycled rubber. Walkway from recycled plastic.  
Connecting clamps from cast aluminum and powder coated

Material Slacklines:  
Steel post from Ø114.3 x 6.3 mm tube, with 6 mm thick steel top plate and 6 x 12 mm thick connecting lugs, all powder coated.  
PUR moulded step on top of post, with combined installed height of 450 mm.  
2 m, 3 m and 4 m long ropes from 16 mm Braided Nylon Rope  
2 m Jungle Rope from 140 mm PP Fendex Rope  
w/10mm Steel-core.

**Tested according to:** DIN EN 1176-1:2017  
DIN EN 1176-11:2014  
EN 1176-1:2017  
EN 1176-11:2014